W-C-581	Conduit and Fittings; Nonmetallic, Rigid, (Bituminized Homogeneous Fiber).	AC 150/5345-3	Specification for L-821 Airport Lighting Panel for Remote Control of Airport Lighting
SS-R-451	Roof-Coating; Asphalt, Brushing-Consistency	AC 150/ 5345-5	Specification for L-847 Circuit Selector Switch, 5,000 Volt 20 Ampere
TT-D-651	Drier, Paint, Liquid	A C 150/5245 7	•
TT-E-487	Enamel; Floor and Deck	AC 150/5345-7	Specification for L-824 Underground Electrical
TT-L-215	Linseed Oil, Raw (For Use in Organic Coatings)		Cables for Airport Lighting Circuits
TT-P-102	Paint, Oil: Titanium- Lead- Zinc and Oil, Exterior, Ready-Mixed,	AC 150/5345-10	Specification for L-828 Constant Current Regulator With Stepless Brightness Control
TT-R-191	White and Light Tints  Red Lead, Dry and  Paste in Oil	AC 150/5345-11	Specification for L-812 Static Indoor Type Constant Current Regulator Assembly; 4 KW and 7.5
TT-T-801	Turpentine; Gum Spirits, Steam Distilled, Sulfate Wood, and		KW; With Brightness Control for Remote Operation
W-C-571	Destructively Distilled  Conduit and Fittings, Nonmetal, Rigid; (Asbestos-Cement or	AC 150/5345-13	Specification for L-841 Auxiliary Relay Cabinet Assembly for Pilot Control of Airport Lighting Circuits
	Fire-Clay Cement), (for Electrical Purposes)	AC 150/5345-18	Specification for L-811 Static Indoor Type Constant
WW-C-581	Conduit, Metal, Rigid; and Coupling, Elbow, and Nipple, Electrical Conduit: Zinc-Coated		Current Regulator Assembly, 4 KW; With Brightness Control and Runway Selection for Direct Operation.
FAA SPECIFICATIONS REFERENCED IN ITEM L-109		AC 150/5345-21 Specification for L-813 Static Indoor Type Constar	
Number AC 150/5340-9	Title Prefabricated Metal Housing for Electrical Equipment		Current Regulator Assembly, 4 KW and 7.5 KW for Remote Operation of Taxiway Lights
	T" F		